

DATASHEET

Chicago Metallic T24 Click 2890




Sounds Beautiful


Chicago Metallic T24 Click 2890

- 24mm grid with universal main runner and joggled end cross tees
- A strong and stable grid which can be easily demounted time and again
- Used to create concealed, semi-concealed and exposed ceiling solutions
- An audible 'click' for fast and accurate installations


Cross-section



Compatible tiles



Coupling



Assortment





Product group		Component description	Height (mm)	Length (mm)	Colour	Pcs per pack	Lm per pack	Kg per pack	Carton per pallet	Kg per pallet
Main runner										
T24 MR CL&HK		Main runner T24 Click / Hook	38	3600	Color-all, 04, 534, 57, 16, 14, 88, 11, 54, 001, 901	15	54	19.5	70	1363
Cross tee										
T24 CT CLICK		Cross tee T24 Click	38	300	Color-all, 88, 11, 001	150	45	13.1	70	916
T24 CT CLICK			38	600	Color-all, 88, 11, 001	45	27	8.2	70	574
T24 CT CLICK			38	1200	Color-all, 88, 11, 001	45	54	15.7	72	1131
T24 CT CLICK			38	1800	Color-all, 88, 11, 001	25	45	16.2	60	972
Wall angle options										
L19x32		Perimeter wall angle trim 32 x 19 x 3050mm	32	3050	Color-all, 88, 11, 001	40	122	27.3	60	1635
F15		F Profile / upstand trim 29 x 16 x 3200mm (panels up to 15mm)	40	3200	001, 11	16	51.2	20.2	50	1010
W8x12		Shadow angle 15 x 12 x 8 x 15 x 3050mm	15	3050	88, 11, 001	30	91.5	17.9	60	1075
L20x25 FLEX ALU		Flexible wall angle 25 x 20 x 3000mm	25	3000	916	10	30	6.9		
Accessories										
SH 50		Suspension clip (curved) for Chicago Metallic T-profiles + securing nail	50			100		2.5		
HDC 4		Steel hold down clip for tile thickness 15-20 mm (A edge)				100		0.3		

Contact Rockfon® for the full range of wall angles and accessories.

Please note that some - not all - products are available in colour. To see which colours are available, please check the assortment table in the relevant Product Datasheet. If you need further assistance or have specific colour preferences, please contact Rockfon.



Position of slots and suspension holes

Product group	Component description	Height (mm)	Length (mm)	Slots	Distance between slots (mm)
T24 MR CL&HK	Main runner T24 Click / Hook	38	3600	36	 50 / 100 / 34 x 100 / 50
T24 CT CLICK		38	300	0	 300
T24 CT CLICK		38	600	1	 300 / 300
T24 CT CLICK		38	1200	3	 300 / 300 / 300 / 300
T24 CT CLICK		38	1800	5	 300 / 300 / 3 x 300 / 300

Components available in special lengths and slottings on request.

Performance



Load bearing capacity

Hanger distance (mm)	Module size (mm)	Kg/m ²	
		2.5 mm	4.0 mm
1200	600 x 600	9.9	16.5
1200	1200 x 600	10.9	17.9
1200	1800 x 600	3.3	5.7



Reaction to fire

A1 / A2-s1,d0 (Color-all)



Corrosion resistance

B



Environment

Fully recyclable

Understanding the performance of Chicago Metallic grids and accessories



Reaction to fire

Reaction to fire is classified in accordance with EN 13501-1. Chicago Metallic steel grids and accessories are non-combustible.



Fire resistance

A range of Chicago Metallic steel grids are tested in combination with different Rockfon tiles and are classified in accordance with European norm EN 13501-2 and/or national norms.



Corrosion resistance

Chicago Metallic products produced from hot dip galvanised steel following the Sendzimir process comply with the corrosion classes of the product standard EN 13964 (A, B, C, D). The standard systems in class B are protected with 100 g/m² zinc evenly applied on both sides. The enhanced corrosion resistance (ECR) systems and accessories in class C or D have respectively a layer of 100 g/m² and 275 g/m² zinc evenly applied on both sides and are protected with an additional layer of 20 micron paint per side.



Load bearing performance

The load bearing performance (max. kg/m² load applicable to the grid system without exceeding the allowable deflection of the individual components) is tested in accordance with the EN 13964 standard. The accumulative value of the system deflection, shown on the data sheets, does not exceed the max. deflection as given in class 1 of the standard. Special project configurations deviating from the standard module sizes mentioned in the data sheets must be calculated by Rockfon technical services.



Colours

Chicago Metallic grids are available in various colours from the RAL and NCS systems, which are measured following the ISO 7724-2 and ISO 7724-3 standards. The actual colours may deviate slightly from the RAL and NCS references.

Chicago Metallic grids are available in a variety of finishes from matt to high gloss, with a respective average of < 5, 15 and 50 units at a 60° angle. The matt finishing is measured at an angle of 85°. See the colour legend for their average values. The gloss unit is measured in accordance with EN13523 part 2.




Cleaning

All Chicago Metallic grids can be cleaned with water and a mild detergent in combination with a melamine foam sponge or microfiber cloth.

Colour legend


Please note that some – not all – products are available in colour. To see which colours are available, please check the assortment table in the relevant Product Datasheet. If you need further assistance or have specific colour preferences, please contact Rockfon.



White 001
RAL 9003



White 901
RAL 9010



White 01
White 916



Matt White 11
RAL 9003

L value: 93
Gloss: 2 at both a 60° and 85° angle



Platinum 54
RAL 7035



Alugrey 04
RAL 9006



Galvanised 00
Galvanised 69




Matt Black 88
RAL 9004

Gloss: 4.5 at 60° angle
and 11.5 at 85° angle



Brushed Alu 534



High Gloss
Chrome 14



Carrara 57




High Gloss
Brass 16




White 001 /
White 001
(8WW)
RAL 9003 /
RAL 9003



Black 08 /
Black 08
(8BB)
RAL 9005 /
RAL 9005




White 001 /
Black 08
(8WB)
RAL 9003 /
RAL 9005



Alugrey
04 /
Black 08
(8GB)
RAL 9006 /
RAL 9005

Rockfon Color-all®




Mustard - 51
NCS S 2050-Y20R



Sand - 30
NCS S 1020-Y30R




Stucco - 20
NCS S 1005-Y20R



Scarlet - 71
NCS S 5040-Y90R




Coral - 76
NCS S 3040-Y90R



Seashell - 75
NCS S 1010-Y70R



Petal - 74
NCS S 1005-Y60R



Seaweed - 34
NCS S 8005-G



Eucalyptus - 32
NCS S 6020-B90G




Sage - 31
NCS S 3010-G10Y




Mint - 12
NCS S 0505-G10Y



Space - 49
NCS S 7020-B




Storm - 48
NCS S 5030-R90B**



Azure - 47
NCS S 3020-B



Fresh - 42
NCS S 2010-B10G



Earth - 25
NCS S 5010-Y50R



Clay - 26
NCS S 5005-G50Y



Linen - 22
NCS S 4005-Y50R



Sandalwood - 13
NCS S 2010-Y70R



Chalk - 21
NCS S 2005-Y40R



Ebony - 28
NCS S 8005-R




Cork - 24
NCS S 4010-Y30R




Hemp - 23
NCS S 3005-Y




Mercury - 62
NCS S 3005-R80B*



Iron - 18
NCS S 7502-B




Concrete - 06
NCS S 5502-B




Mastic - 17
NCS S 4000-N




Zinc - 05
NCS S 4005-R50B



Charcoal - 09
NCS S 8500-N



Anthracite - 08
NCS S 7005-B



Gravel - 03
NCS S 3502-B



Plaster - 02
NCS S 2005-R80B



Stone - 01
NCS S 2000-N



Moon - 10
NCS S 1005-R80B

* Colour contains effect pigments.

** Colour is between NCS S 5030-R90B and NCS S 6030-R90B.

Please note that some – not all – products are available in colour. To see which colours are available, please check the assortment table in the relevant Product Datasheet. If you need further assistance or have specific colour preferences, please contact Rockfon.

NCS codes are closest colour match. The actual colour of the Rockfon Color-all® grid may deviate slightly from printed colours due to the texture of the surface.

Samples are available upon request.

Sounds Beautiful

